



Features:

- ▶ ABS plastic moulding
- ▶ Apertures accepting a wide range of bus bar
- ▶ CTs are ultrasonically welded and unbreakable



Advantages:

- ▶ Easy bus bar mounting
- ▶ Highly cost effective
- ▶ Compact in size

Applications:

- ▶ Switchgear
- ▶ Distribution system
- ▶ Generator sets
- ▶ Control Panels
- ▶ Control Devices
- ▶ Overload protection

Input Specifications

Rated Primary Current	400A to 4000A (any other on request)
Rated Secondary Output	5A/1A (Consult factory)

Technical Specifications

Rated Burden	5VA, 10VA, 15VA & 30VA (any other on request)
Class of Accuracy	0.2s, 0.5 and 1
Thermal Nominal Continuous Rated Current	1.2 times rated current continuously
Thermal Short Circuit Current	2.55x Ith
Insulation Class	60xIn
Max. Operating Voltage	Class E
Insulation Test Voltage	720V maximum
Compliance Standard	3KV AC for 1 minute
	VE404 and IEC185

Ordering Information

Ordering Code	Ratio	Class	Burden (VA)
VIPS 1201-400/5-0.5-5	400/5	0.5	5
VIPS 1201-500/5-0.5-5	500/5	0.5	5
VIPS 1201-600/5-0.5-5	600/5	0.5	5
VIPS 1201-750/5-0.5-10	750/5	0.5	10
VIPS 1201-800/5-0.5-10	800/5	0.5	10
VIPS 1201-1000/5-0.5-15	1000/5	0.5	15
VIPS 1201-1200/5-0.5-15	1200/5	0.5	15
VIPS 1201-1250/5-0.5-15	1250/5	0.5	15
VIPS 1201-1500/5-0.5-15	1500/5	0.5	15
VIPS 1201-1600/5-0.5-15	1600/5	0.5, 0.2s	15
VIPS 1201-2000/5-0.5-15	2000/5	0.5	15
VIPS 1201-2400/5-0.5-15	2400/5	0.5, 0.2s	15
VIPS 1201-2500/5-0.5-15	2500/5	0.5	15
VIPS 1201-3000/5-0.5-30	3000/5	0.5	30
VIPS 1201-4000/5-0.5-30	4000/5	0.5	30
OTHER RATIO			

Environmental Specification

Operating Temperature	20°C to 70°C
Storage Temperature	0° to 55°C
Humidity	<95% RH

Dimensions

